Corotop[®] FIX

Corotop[®]

TAPES

SET I LENK

ENG/TAS/CFI/042017 AKT/12.04.2017

Description	Adhesive tape for membranes
Material	PE foil with acrylic dispersion, reinforced with polyester fibre mesh
Spacer	Silicone
Thickness	0.26-0.29mm
Properties	The multiseasonal single-sided adhesive tape. It is produced from the acrylic dispersion reinforced with polyester fibres to have better adhesiveness properties.
Application	 for bonding and fixing the polypropylene and polyethylene plastic foils for connecting foil with plastics, concrete, wood and metal to be used inside building structures
Advantages	 bonds following membranes' and foils' layers together connects foils with other plastics; effecitvely repairs damages universal- to be used on both smooth and rough surfaces resistant to oils as well as acid and alkaline enivronment

See Not

-

Technical data	
Length [m]	25
Width [mm]	50
Color	White foil with red imprint
Operating temperature	From -10°C (recommended 5°C) to 40°C
Temperature resistance	Od -40°C do +80°C
Tear Resistance	≥20N /25mm
Elongation	≥20N /25mm; 100%
Package	12
Number on pallet [pc.]	840
Pallet dimensions	1200 x 800 x 1800
Product weight [kg]	0,47
Pallet weight [kg]	425
Bar code	5903364600297

Assembly and storage		
How to use/ Assembly instructions	Bonded surfaces should be dry, free of any dirt, grease, and sludge. Do not tighten the tape on the bonding surface. Observe the recommended temperature for using.	
Conditions of use and storage	Keep in the temperature for using, in closed and dry containers. The product is covered by a guarantee provided strict compliance with the guidelines contained in the data sheet. The producer reserves the right to refuse to recognise a claim in case of any failure to comply with the recommended guidelines.	



TAPES

Corotop

The information, recommendations and hints have been provided in good faith on the basis of our best knowledge, research and experience. We assume no responsibility for effects of improper or invalid use of our products. Every user of this material has to ascertain, using all possible means, including checking of the end products under the proper conditions, of usability of the materials delivered for the defined purpose.

Product information can be found on the Web page www.corotop.com.pl